



The Superior Choice:
Translucent-Selective Films



HÜPER SELECT DREI

Specifications	Single Pane	Double Pane
Visible Light Transmission	35%	31%
Visible Light Reflectance	12%	12%
Shading Coefficient	0.35	0.48
Solar Heat Gain Coefficient	0.30	0.42
Infrared Rejection	98%	98%
UV Light Rejection	99.9%	99.9%
Total Solar Energy Rejected	70%	58%
Glare Reduction	61%	64%
U-value	1.04	0.47

www.huperoptikusa.com



Performance data is based on this film being applied to the inside of 3mm clear glass. All data calculated using the definitions and equations in ISO9050 & ASHARE Handbook. The data is subject to variations within industry standards.
Copyright © 2013 Hüper Optik® USA (www.huperoptikusa.com), 5821 W. Sam Houston Pkwy N., Suite 400, Houston, TX 77041; phone: 888.296.3456; fax: 832.467.1190



Meister Keramische Technologie

HÜPER OPTIK®

Nano-Ceramic Window Films



The Smarter Choice:
Nano-Ceramic Films



Powered by
**Meister
Keramische
Technologie**



HÜPER CERAMIC 30

Specifications	Single Pane	Double Pane
Visible Light Transmission	30%	29%
Visible Light Reflectance	11%	12%
Shading Coefficient	0.43	0.56
Solar Heat Gain Coefficient	0.37	0.49
Infrared Rejection	86%	86%
UV Light Rejection	99.9%	99.9%
Total Solar Energy Rejected	63%	51%
Glare Reduction	62%	64%
U-value	1.04	0.47

www.huperoptikusa.com



Performance data is based on this film being applied to the inside of 3mm clear glass. All data calculated using the definitions and equations in ISO9050 & ASHARE Handbook. The data is subject to variations within industry standards.
Copyright © 2013 Hüper Optik® USA (www.huperoptikusa.com), 5821 W. Sam Houston Pkwy N, Suite 400, Houston, TX 77041; phone: 888.296.3456; fax: 832.467.1190



HSPE-C30



Meister Keramische Technologie