



Window Film Specification

The window films listed below are frequently selected by our customers.
 Several other products are available for review and consideration.
 Our specialists will be happy to present other options.



VLT = Visible Light Transmission
 VLR = Visible Light Reflection
 UV = Ultraviolet Rejection
 GR = Glare Reduction
 TSER = Total Solar Energy Rejected

Performance Data

is based upon the film being applied to the inside of a DUAL pane clear glass window.

The data is subject to variation within industry standards.

	<u>VLT</u>	<u>VLR</u>	<u>UV</u>	<u>GR</u>	<u>TSER</u>
<u>INTELIGENTE</u> Series:					
• Cool Touch IR	64%	13%	99%	33%	56%
<u>PERFORMANTE</u> Series:					
• Glare 15	16%	11%	99%	85%	61%
• Calm 40	35%	13%	99%	59%	56%
• Clear 70	63%	14%	99%	32%	50%
<u>NANO CERAMIC</u> Series:					
• C-30	30%	17%	99%	66%	52%
• C-40	40%	18%	99%	54%	46%
• C-55	49%	16%	99%	42%	44%
<u>NANO METALLICO</u> Series:					
• Blend 5	5%	60%	99%	93%	70%
• DN 15	11%	23%	99%	89%	61%
• Silver	15%	60%	99%	83%	72%
• Blend 20	15%	49%	99%	82%	66%
• Blend 35	32%	27%	99%	61%	44%